

ALL WE NEED TO KNOW FROM YOU IS:

- the profile
- the pressure
- the dimensions
- the medium (or media)
- the operating temperature
- the slide speed

OUR STANDARD MATERIALS COVER:

- **Oz - SR (purple) - Super Red**
Hardness: 95+ to -2 Shore A
Pressure: up to 500 bar
Temperature: -50 to +120°C
- **Oz - UP (violet) - Ultra Performance**
Hardness: 95+ to -2 Shore A
Pressure: up to 500 bar
Temperature: -20 to +120°C
- **Oz - Egrin (green)**
Hardness: 95+ to -2 Shore A
Pressure: up to 500 bar
Temperature: -50 to +120°C
- **Oz - Food Grade Polyurethane**
Hardness: 95+ to -2 Shore A
Pressure: up to 500 bar
Temperature: -20 to +110°C
- **Oz - TUF (blue)**
Temperature: -50 to +100°C
- **Oz - NBR (black)**
Hardness: 85+ to -5 Shore A
Pressure: up to 160 bar
Temperature: -30 to +100°C
- **Oz - HNBR (black)**
Short temperature of up to +170°C,
up to +150°C (extended periods)
Pressure: up to 160 bar
- **Oz - NEO (black)**
Hardness: 85+ to -2 Shore A
Neoprene rubber
- **Oz - VITON (brown)**
Hardness: 85+ to -5 Shore A
Pressure: up to 160 bar
Temperature: -20 to +200°C
- **Oz - AFLAS**
Hardness: 85+ to -5 Shore A
Temperature: -10 to +200°C
- **Oz - EPDM (black)**
Hardness: 85+ to -5 Shore A
Pressure: up to 160 bar
Temperature: -30 to +130°C
- **Oz - SIL (white)**
Hardness: 85+ to -5 Shore A
Temperature: -60 to +200°C
- **Oz - PTFE (white)**
Bearing Pressure: 2N/mm
Temperature: -200 to +260°C
- **Oz - TMF (multifibre)**
Bearing Pressure: 3N/mm
Temperature: -200 to +260°C
- **Oz - TFG (graphite-carbon)**
Bearing Pressure: 3N/mm
Temperature: -200 to +260°C
- **Oz - Mo (black or grey)**
Temperature: -50 to +150°C
- **Oz - Rot (red)**
Temperature: -50 to +150°C

WE SUPPLY YOU WITH:

- Seals up to 2000mm in diameter
- Any custom-made seal
- Urethanes, rubbers, teflon, plastics and more
- One hour service, if required
- One-off and large quantities
- Over 200 standardised profiles
- Metric or imperial dimensions
- Highest quality and fastest delivery

WWW.OZSEALS.COM



ABN 11 110 274 38 • ACN 110 274 38

QUEENSLAND

8 Aranda Street Slacks Creek QLD 4127
Tel: (07) 3290 1846
Fax: (07) 3208 6235
Mobile: 0419 119 224
Email: wil@ozseals.com

NEW SOUTH WALES

Tel: (02) 9620 8382
Fax: (02) 9620 8381

VICTORIA

Unit 9, 67-75 Garden Drive
Tullamarine VIC 3043
Tel: (03) 9335 5699
Fax: (03) 9335 5799

















Profiles & Materials



1300 792 600

1300 792 600

GLAND GS SEALS										
										
										
										
PISTON PK SEALS										
										
										
										
QUATRO QA SEALS										
										
										
										
WA WIPERS										
										
										
										
GUIDE GF RINGS										
										
										
										
BACKUP BST RINGS										
HIGH PRESSURE HR ROTARY SEALS										