OZ 5000X

Features

- Machining seals up to a diameter of 570mm
- Manufacture seals at high speeds of up to 2000rpm
- 45° integral slant bed
- Uses the Servo motor on its spindle
- Fully equipped with swarf extraction system and toolbox
- Hydraulic chuck and hydraulic tailstock
- Option to utilise VDI Power tool turret
- CAD/CAM software developed exclusively by Oz Seals.

Highlights

- Seal manufacturing software and hardware
- OZ Seal Turn CAD/CAM Software
- OZ Seals Fitting Manufacturing Software Computer
- Swarf Extraction System
- Toolbox (holders, cutting tools and spares)





















Specification :

Item	Specification	Unit	
Capacity	Max. swing dia. over bed	mm	Ф570
	Max. swing dia. over slide	mm	Ф320
	Recommended turning dia.	mm	Ф250
	Max. turning dia	mm	Ф360
	Max. turning length	mm	450/750/1350/2000/3000
Spindle	Spindle bore	mm	Ф86
	Spindle type	1	A2-8
	Spindle speed	rpm	2000
	Chuck size	1	10"
	Max. bar through dia.	mm	Ф 74
	Spindle motor power	Kw	11(15)
X/Z axes	X axes travel	mm	250
	Z axes travel	mm	600/1000/1500/2150/3150
	X/Z axes rapid moving speed	m/min	20/16
Tool turret	Tool turret type	mm mm / rpm / mm Kw mm	Hydraulic 8 station
	Toolshank size	mm	25x25, Φ40
Tailstock	Max. turning length Spindle Spindle bore Spindle type Spindle speed Chuck size Max. bar through dia. Spindle motor power X/Z axes X axes travel Z axes travel X/Z axes rapid moving speed Tool turret type Toolshank size Istock Tailstock quill taper Tailstock guideway	1	MT5# (for 600mm) MT4# rotary (for other)
	Tailstock quill dia./travel	mm	Φ75/100 (for 600mm) Φ110/100 (for other)
	Tailstock guideway	/	Rectangle guideway
Others	Machining roughness	mm	Ra≤1.6
	Machining accuracy	1	IT6
	X/Z axes repeated positioning accuracy	mm	0.006/0.008 (0.01,0.013,0.017,0.021)
	Overall size	mm	3200x1900x1900
	N.W.	kg	3600

Main parts list:

Item	Brand	
CNC controller	OPT: SIEMENS/FANUC/GSK	
Feeding driver & motor	OPT: SIEMENS/FANUC/GSK	
Spindle driver & motor	OPT: SIEMENS/FANUC/GSK	
Spindle unit	TAIWAN-LOSEN/KENTURN	
Spindle encoder	GERMANY-HEIDENHAIN	
Servo powered tool turret	GERMANY-SAUTER	
Ball screw	TAIWAN-PMI/HIWIN	
Ball screw bearing	JAPAN-NSK/TAIWAN-TPI	
Linear guideway	TAIWAN PMI/HIWIN	
Lubrication system	TAIWAN-ISHAN	
Rotary oil cylinder & chuck	TAIWAN-CH-H	
Hydraulic parts	TAIWAN/JAPAN	
Coolant pumps	Joint-venture	
MPG	USA-HEDSS	

ltem	Brand	
Tri-colour indication lamp	KOREA-QLIGHT	
Isolation transformer	CHINA-top-CHINT/JIUKO	
Breaker	FRANCE-SCHNEIDER	
AC contactor	FRANCE-SCHNEIDER	
Relay	JAPAN-OMRON	
Dc switching mode power supply	TAIWAN-MEANWELL	
Terminal block	GERMANY-WEIDMULLER	
Synchronous belt	USA-GATES	
Synchronous belt wheel	TAIWAN - PTP	
Nuts	TAIWAN-YINSH	
Shaft coupling	GERMANY-KTR/R+W	
Extensible cover	TAIWAN-WANHE	
Chip conveyor & chip bucket	TAIWAN-WANHE	
Coolant pipe	TAIWAN-WEIDING	